Log Everything, Alert Smarter
See how AI accelerates triage, playbooks, and investigation across your SecOps workflow.
Re

DATA SCIENCE

Knowledge Graph Transfo Architecting Dynamic Rea for Evolving Knowledge

Artificial intelligence software was used to enhance flow, and readability of this article's text.

Anthony Alcaraz
Oct 28, 2023 9 min read

Artificial intelligence software was used to enh grammar, flow, and readability of this article's t

Knowledge graphs, which represent facts as ir entities, have emerged as a pivotal technique d c

sly e t ca d.

his r incorporating a temporal dimension, with each

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

Customise Reject All Accept All

tagged with a timestamp denoting its period of validity. TKGs allow modeling not only the connections between entities but also the dynamics of these relationships, unlocking new potentials for AI.

While TKGs have garnered substantial research attention, their application in specialized domains remains an open frontier. In particular, the financial sector possesses attributes like rapidly evolving markets and multifaceted text could significantly benefit from dynamic know However, underdeveloped access to high-quali knowledge graphs has constrained advances i

Addressing this gap, Xiaohui Victor Li(2023) int innovative, open-source Financial Dynamic Kn (FinDKG) powered by a novel temporal knowle learning model named Knowledge Graph Trans (KGTransformer).

FinDKG/FinDKG_dataset at main · xiaohui-v

Financial Dynamic Knowledge Graph

glol late ers fran nera k m

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

The KGTransformer model, designed to handle the intricacies of TKGs, is shown to outperform existing static knowledge graph models on benchmark TKG datasets.

The architecture leverages recent advances like meta-relation modeling, graph attention networks, and temporal point processes to achieve strong results.

Through access to open-sourced resources lik
KGTransformer, and the fine-tuned Integrated
Knowledge Graph Generator (ICKG) model, this
catalyze interdisciplinary research at the inters
knowledge graphs and finance.

By harnessing dynamic knowledge graphs to g
nuanced financial insights, this research highli
directions for injecting structured knowledge i
finance and economics.

The capabilities showcased through FinDKG ur
power of knowledge graphs in capturing the fl
of the real world.

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

ote
GTs
nd ic
ning
s st
sys
in dynamic understanding.

Limitations of Static Graph Networks

Most existing graph neural networks are designed for static graphs and do not account for temporal dynamics. For instance, models like Graph Convolutional Networks (GCNs) and Graph Attention Networks (GATs) aggregate information from neighboring nodes disregarding any temporal patterns.

This static assumption severely restricts their capacity on TKGs. Without considering tempor predictions made using static embeddings qui outdated as the graph evolves.

Furthermore, static models treat all edges uni the nuance to model relationships that vary in validity over time. Their representation also re to immediate neighbors, lacking a broader tem perspective.

TKGs require models that can understand time edge importance, adapt their decision-making and entities evolve, and make predictions whil both past and future implications.

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

At their core, KGTs incorporate **inductive biases** that make their design uniquely suited for TKG-based reasoning. These include:

- **Explicit temporal modeling** to capture evolutionary dynamics
- **Multi-relational handling** to represent heterogeneous relationships
- **Continuous entity tracking** to allow tempo
- **Graph-level summarization** to enable broa

Let's break down how KGTs implement these c

Explicit Temporal Modeling

KGTs use separate entity and relation RNNs (R Networks) to model the temporal evolution of embeddings.

As new events get added to the TKG, the RNNs embeddings to reflect the new state. This allo a representation of how an entity or relationsh

node

este

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

In line with recent multi-relational graph network advances, KGTs employ relation-specific parameters to handle varied semantic connections.

For example, the "Employed_By" and "Friends_With" relations have very different implications, which the model captures using distinct weights for each relation type.

This nuanced handling prevents over-generaliz
improves predictive quality.

Continuous Entity Tracking

Instead of processing the TKG in isolated snap
continuously update embeddings as new even
the graph.

This allows smoothly tracking entities over tim
re- initializing at each timestep. The resulting
preserves temporal contexts and enables the
as the TKG evolves.

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

Ts a
e en
im
pact
spanning beyond immediately affected entities

The graph embedding is calculated using a temporal attention mechanism over all nodes, enabling adaptive and efficient summarization.

Architectural Components

KGTs comprise several interconnected components that impart the aforementioned capabilities:

- **Input Layer:** Accepts initial node features
- **Temporal Embeddings:** Serve as specialize encoding time-evolving properties using R
- **Structural Embeddings:** Capture node neig global topology through attentive message between neighbors.
- **Position Encodings:** Provide temporal awa absolute positions analogous to transform architectures.
- **Feed Forward Layers:** Enable deeper sema using multi-layer perceptrons.
- **Output Layer:** Returns node embeddings c

LATEST
EDITOR'S PICKS
DEEP DIVES
NEWSLETTER
WRITE FOR TDS
Sign in
Submit an Article

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

arch
eddi
cal a
izat
wou

incorporated into the equations.

1. Input Layer:

$$[\mathbf{X} \in \mathbb{R}^{n \times d}]$$

- Where$(\mathbf{X})$ is the input matrix.
- (n) is the number of nodes.
- $(d)$is the dimensionality of initial node features or embeddings.

2. Temporal Embeddings (using RNNs):

$$[\mathbf{H}^{(t)} = RNN(\mathbf{X}, \mathbf{H}^{(t-1)})]$$

- Where$(\mathbf{H}^{(t)})$ is the temporal embedding at time (t).
- (RNN) represents the recurrent neural network function.
- $(\mathbf{H}^{(t-1)})$is the temporal embedding from the previous time step.

3. Structural Embeddings (using attentive message passing):

$$[\mathbf{M}i = \sum j \in \mathcal{N}(i)\alpha_{ij}\mathbf{H}j][\alpha ij = \frac{\exp(\mathbf{a}(\mathbf{H}_i,\mathbf{H}j))}{\sum k\in\mathcal{N}(i)\exp(\mathbf{a}(\mathbf{H}_i,\mathbf{H}_k))}]$$

- Where $(\mathbf{M}_i)$is the structural embedding for node(i).
- $(\mathcal{N}(i))$ is the set of neighboring nodes of(i).
- (α_{ij}) is the attention weight between node$(i)andnode(j)$.
- $(\mathbf{a})$represents the attention mechanism.

4. Position Encodings:

$$[\mathbf{P}^{(t)} = \text{PositionEncoding}(\mathbf{H}^{(t)})]$$

- Where$(\mathbf{P}^{(t)})$provides temporal awareness of absolute positions at t

5. Feed Forward Layers (using multi-layer perceptrons):

$$[\mathbf{F}^{(l)} = \sigma(\mathbf{W}^{(l)}\mathbf{H}^{(l-1)} + \mathbf{b}^{(l)})]$$

- Where $(\mathbf{F}^{(l)})$ is the output after the $(l) - th$feed-forward layer.
- $(\mathbf{W}^{(l)})$and $(\mathbf{b}^{(l)})$are the weight matrix and bias vector for the (l) -
- (\sigma) is an activation function.

6. Output Layer:

utput

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

ods

The unique architectural attributes of KGTs lend them multiple advantages over previous state-of-the-art models on temporal graphs:

- **Generalization:** KGTs can handle previously unseen entities, relations, and events by leveraging the learned inductive biases. Comparatively, many existing models rely on re-training.
- **Reasoning:** The temporally-enriched entity representations learned by KGTs lead to in predictive reasoning on temporal graphs o previous models.
- **Efficiency:** Mechanisms like the graph eml having to process lengthy historical seque training and inference efficiency on large T
- **Interpretability:** Components like relation- parameters and temporal attention provid the model's working, improving interpretab box models.

Overall, KGTs advance the state-of-the-art in reasoning on temporal knowledge graphs. Thei ecti rob ne-

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

The introduction of KGTs stimulates intriguing opportunities at the intersection of knowledge representation, reasoning, and time-series modeling – opening new frontiers in dynamic graph learning. As TKGs find expanding real-world applications, KGTs signify an impactful step towards endowing AI agents with a temporal understanding of the world around them.

This research makes significant strides in adva
modeling of evolving real-world systems using
knowledge graphs and specialized learning tec
Through the introduction of an open-source Fi
Knowledge Graph (FinDKG) and an innovative K
Graph Transformer (KGTransformer) model, thi
both practical tools and methodological advan

The creation of FinDKG from a corpus of globa
demonstrates the feasibility of constructing dc
dynamic knowledge graphs.

FinDKG encapsulates both qualitative and qua
aspects of financial systems in an interconnec
framework. The use cases presented, from risk
ty in
al is
G as

pus
ph
combining architectural elements like graph at

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

networks, meta-relation modeling, and temporal point processes, KGTransformer achieves strong performance on benchmark dynamic graph datasets. The model is shown to outperform existing static knowledge graph models that do not account for temporal contexts. The introduction of components like relation-specific parameters and continuous entity tracking provide more expressive representations to handle evolving graphs.

The innovations presented in this research cat
possibilities at the intersection of knowledge r
reasoning, and time-series modeling.

The availability of open-sourced resources like
KGTransformer, and the ICKG language model
ground for other researchers to build upon thi
expand such techniques to new domains.

Some promising directions include:

- Constructing dynamic knowledge graphs f
verticals like healthcare, education, transp
that can benefit from temporal reasoning.

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

- Empirical comparisons of graph learning techniques with traditional time-series models on temporal forecasting tasks.
- Architectural improvements to KGTransformer like incorporating transformer encoders or improving temporal memory.

By harnessing the dual powers of transformer
structured knowledge graphs, this research en
dynamic understanding critical for intelligent s
operating in the real world.

As knowledge representation and reasoning ov
open frontiers, the groundwork established he
springboard for impactful innovation at the co
machine learning and symbolic AI.

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

Image by the author

LATEST

EDITOR'S PICKS

DEEP DIVES

NEWSLETTER

WRITE FOR TDS

Sign in

Submit an Article

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

WRITTEN BY

Anthony Alcaraz

See all from Anthony Alcaraz

AI Data Data Science Deep Learning Machine Learning

Share This Article

**Towards Data Science is a community p
Submit your insights to reach our global a
earn through the TDS Author Payment**

Write for TDS

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.



ARTIFICIAL INTELLIGENCE

Implementing Convolutional Neural Networks in TensorFlow

Step-by-step code guide to building a Convolutional Neural Network

Shreya Rao
August 20, 2024 6 min read

ARTIFICIAL INTELLIGENCE

How to Forecast Hierarchical Time Series

A beginner's guide to forecast reconciliation

Dr. Robert Kübler
August 20, 2024 13 min read



DATA SCIENCE

Hands-on Time Series Anomaly Detection using Autoencoders, with Python

Here's how to use Autoencoders to detect signals with anomalies in a few lines of...

Piero Paialunga
August 21, 2024 12 min read

MACHINE LEARNIN

3 AI Use Case Chatbot)

Feature engineer unstructured dat

Shaw Talebi
August 21, 2024 7

DATA SCIENCE



asic
n ar

An illustrated gui
learning concept

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

Shreya Rao

February 3, 2023 6 min read



DATA SCIENCE

Must-Know in Statistics: The Bivariate Normal Projection Explained

Derivation and practical examples of this powerful concept

Luigi Battistoni

August 14, 2024 7 min read

Yo blica
da ificia
pr

©

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.

Subscribe to Our Newsletter

WRITE FOR TDS · ABOUT · ADVERTISE · PRIVACY POLICY · TERMS OF USE

LATEST

EDITOR'S PICKS

DEEP DIVES

NEWSLETTER

WRITE FOR TDS

Sign in

Submit an Article

We value your privacy

We use cookies to enhance your browsing experience, serve personalised ads or content, and analyse our traffic. By clicking "Accept All", you consent to our use of cookies.